



EV Charger Proposal

AGILITY 敏捷

TB-332 Series



TB-332EA-7

Wall-Mount AC EV Charger 7.2kW



Specifications	
Power	7.2KW
Input/Output	230VAC/230VAC
Output current	32A
Over temperature protection	≥95℃
Rated residual operating current	AC30mA+DC6mA
Operating temperature	‘-30℃- +50℃
Storage temperature	‘-40℃- +85℃
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥8796h
Start method	Plug and play/RFID card/App
Maximum altitude	2000m
Communication	WIFI+BLE/4G Optional
Connector type	IEC 62196-2 Type 2
Cable length	5 meters (Customizable)
Weight	5 Kg (with cable)
Wiring method	Enter and out at the bottom
Protection	Connector IP54, Host IP66 & IK10
Host dimension	353*256*113(mm)

TB-316EA-11 Wall-Mount AC EV Charger 11kW



Specifications	
Power	11KW
Input/Output	400VAC/400VAC
Output current	16A
Over temperature protection	≥95℃
Rated residual operating current	AC30mA+DC6mA
Operating temperature	‘-30℃- +50℃
Storage temperature	‘-40℃- +85℃
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥8796h
Start method	Plug and play/RFID card/App
Maximum altitude	2000m
Communication	WIFI+BLE/4G Optional
Connector type	IEC 62196-2 Type 2
Cable length	5 meters (Customizable)
Weight	5 Kg (with cable)
Wiring method	Enter and out at the bottom
Protection	Connector IP54, Host IP66 & IK10
Host dimension	353*256*113(mm)

TB-332EA-22 Wall-Mount AC EV Charger 22kW



Specifications	
Power	22KW
Input/Output	400VAC/400VAC
Output current	32A
Over temperature protection	≥95℃
Rated residual operating current	AC30mA+DC6mA
Operating temperature	‘-30℃- +50℃
Storage temperature	‘-40℃- +85℃
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥8796h
Start method	Plug and play/RFID card/App
Maximum altitude	2000m
Communication	WIFI+BLE/4G Optional
Connector type	IEC 62196-2 Type 2
Cable length	5 meters (Customizable)
Weight	5 Kg (with cable)
Wiring method	Enter and out at the bottom
Protection	Connector IP54, Host IP66 & IK10
Host dimension	353*256*113(mm)